

CLAIMS

What is Claimed is:

1. An optical position-tracking system comprising:
a first light beam steering device for sweeping a first light beam
5 through a first angular range to cause a reflection of said first light beam by a target; and
a second light beam steering device for sweeping a second light beam through a second angular range to cause a reflection of said second light beam by said target, wherein a position of said target is determined
10 using a triangulation technique utilizing a first angular value of said first light beam and a second angular value of said second light beam, and wherein said first angular value and said second angular value depend on the existence of said respective reflection.
- 15 2. The optical position tracking system as recited in Claim 1 further comprising a processing unit for determining said position of said target.
- 20 3. The optical position-tracking system as recited in Claim 1 wherein said position of said target is an absolute position.
4. The optical position-tracking system as recited in Claim 1 wherein said target includes a retro-reflecting surface.
- 25 5. The optical position-tracking system as recited in Claim 1 wherein if said target reflects said first light beam when said first light beam is at a particular angular value, said first light beam steering device sweeps said first light beam through a limited angular range that includes said particular angular value until said target fails to reflect said first light beam.
30

6. The optical position-tracking system as recited in Claim 1 wherein if said target reflects said second light beam when said second light beam is at a particular angular value, said second light beam steering device sweeps said second light beam through a limited angular range that
5 includes said particular angular value until said target fails to reflect said second light beam.

7. The optical position-tracking system as recited in Claim 1 wherein said first light beam steering device and said second light beam
10 steering device are each selected from a group consisting of a MEMS (microelectromechanical system) motor beam steering device, a galvanometer beam steering device, an acousto-optic beam steering device, an electro-optic beam steering device, a grating structure beam steering device, a holographic structure beam steering device, and a scanning mirror
15 beam steering device.

8. The optical position-tracking system as recited in Claim 1 wherein said first light beam and said second light beam are each generated by a light source selected from a group consisting of an
20 incandescent technology-based light source, a LED (light emitting diode) technology-based light source, a semiconductor laser technology-based light source, and a rare-earth laser technology-based light source.

9. A system comprising:
25 a first light beam steering device for sweeping a first light beam through a first angular range to cause a reflection of said first light beam by a target;

a second light beam steering device for sweeping a second light beam through a second angular range to cause a reflection of said
30 second light beam by said target, wherein a position of said target is determined using a triangulation technique utilizing a first angular value of

said first light beam and a second angular value of said second light beam,
and wherein said first angular value and said second angular value depend
on the existence of said respective reflection; and

5 a computer system for receiving and using said position of said
target.

10 10. The system as recited in Claim 9 further comprising a
processing unit for determining said position of said target.

11. The system as recited in Claim 9 wherein said position of said
10 target is an absolute position.

12. The system as recited in Claim 9 wherein said position enables
controlling a cursor in said computer system.

15

13. The system as recited in Claim 9 wherein said position enables
inputting data into said computer system.

14. The system as recited in Claim 9 wherein said target includes a
20 retro-reflecting surface.

15. The system as recited in Claim 9 wherein if said target reflects
said first light beam when said first light beam is at a particular angular
value, said first light beam steering device sweeps said first light beam
25 through a limited angular range that includes said particular angular value
until said target fails to reflect said first light beam.

16. The system as recited in Claim 9 wherein if said target reflects
said second light beam when said second light beam is at a particular
30 angular value, said second light beam steering device sweeps said second

light beam through a limited angular range that includes said particular angular value until said target fails to reflect said second light beam.

17. The system as recited in Claim 9 wherein said first light beam
5 steering device and said second light beam steering device are each
selected from a group consisting of a MEMS (microelectromechanical
system) motor beam steering device, a galvanometer beam steering device,
an acousto-optic beam steering device, an electro-optic beam steering
device, a grating structure beam steering device, a holographic structure
10 beam steering device, and a scanning mirror beam steering device.

18. The system as recited in Claim 9 wherein said first light beam
and said second light beam are each generated by a light source selected
from a group consisting of an incandescent technology-based light source, a
15 LED (light emitting diode) technology-based light source, a semiconductor
laser technology-based light source, and a rare-earth laser technology-
based light source.

19. A method of optically tracking a target, said method comprising:
20 sweeping a first light beam through a first angular range at a first
location and determining a first angular value of said first light beam;
sweeping a second light beam through a second angular range at a
second location and determining a second angular value of said second
light beam; and
25 when said target causes a reflection of said first and second light
beams, determining a position of said target using a triangulation technique
utilizing said first and second angular values which depend on the existence
of said respective reflection.

20. The method as recited in Claim 19 wherein said position of
30 said target is an absolute position.

21. The method as recited in Claim 19 wherein said target includes a retro-reflecting surface.

5 22. The method as recited in Claim 19 wherein said sweeping said first light beam step includes:

 if said target reflects said first light beam when said first light beam is at a particular angular value, sweeping said first light beam through a limited angular range that includes said particular angular value until said target
10 fails to reflect said first light beam.

23. The method as recited in Claim 19 wherein said sweeping said second light beam step includes:

 if said target reflects said second light beam when said second light
15 beam is at a particular angular value, sweeping said second light beam through a limited angular range that includes said particular angular value until said target fails to reflect said second light beam.

24. The method as recited in Claim 19 wherein said sweeping said
20 first light beam step is performed by a first light beam steering device, wherein said sweeping said second light beam step is performed by a second light beam steering device, and wherein said first light beam steering device and said second light beam steering device are each selected from a group consisting of a MEMS (microelectromechanical
25 system) motor beam steering device, a galvanometer beam steering device, an acousto-optic beam steering device, an electro-optic beam steering device, a grating structure beam steering device, a holographic structure beam steering device, and a scanning mirror beam steering device.

30 25. The method as recited in Claim 19 wherein said first light beam and said second light beam are each generated by a light source selected

10030169-1

from a group consisting of an incandescent technology-based light source, a LED (light emitting diode) technology-based light source, a semiconductor laser technology-based light source, and a rare-earth laser technology-based light source.

5